

ELECTRIC SERIES SCISSOR LIFTS

0407SE(1530SE)/0607SE(1932SE)

Compliance with ISO/CE/EAC standards

PRODUCT HIGHLIGHTS

- Easily passes through standard doors and can access elevators
- The short design of sliding rail makes debris easy to clean
- Bumper rail and indented sliding rail designed for anti-scratch
- DC motor drive, giving a longer runtime



Standard features

Maintenance-free battery	Automatic braking system	Drive at full height
Proportional control	Emergency lowering system	Forklift pocket and lifting eyes
Bumper rail	Emergency stop at both platform and ground controls	Electrophoresic paint technology
2WD x 2WS	Fault diagnosis system	Foldable guardrail
Non-marking tyres	Tilt protection	Overload sensing system
Integrated hand shield	Automatic pothole guard	

Optional features

Overhead anti-collision device	Headlight	RCBO
AC power to platform	Foot switch	

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

ELECTRIC SERIES SCISSOR LIFTS

0407SE(1530SE)/0607SE(1932SE)

Compliance with ISO/CE/EAC standards

Model	0407SE(1530SE)	0607SE(1932SE)
Dimensions		
Max Working Height(Indoor/Outdoor)	6.5m/5.8m(21'4"/19')	7.6m/6.6m(24'11"/21'26")
A Max Platform Height(Indoor/Outdoor)	4.5m/3.8m(14'9"/12'6")	5.6 m/4.6m(18'5"/15')
B Max Horizontal Extension	0.6m(2')	0.6m(2')
C Length-Stowed	1.42m(4'8")	1.52m(4'12")
D Width-Stowed	0.76m(2'6")	0.81m(2'8")
E Height-stowed (Rail Folded)	1.67m(5'6")	1.77m(5'10")
E Height-stowed (Rail Unfolded)	1.97m(6'6")	2.1m(6'11")
F Wheelbase	1.11m(3'8")	1.13m(3'9")
Ground Clearance(Pothole Guard Stowed)	0.061m(2.4")	0.065m(2.6")
Ground Clearance(Pothole Guard Deployed)	0.02m(0.75")	0.025m(0.98")
Platform Dimensions(LxWxH)	1.34mx0.7mx1.1m(4'5"x2'4"x3'7")	1.37mx0.7mx1.1m(4'6"x2'4"x3'7")
Performance		
Platform Allowable Occupants	2 persons(indoor) 1 person(outdoor)	2 persons(indoor) 1 person(outdoor)
Platform capacity	240kg(529lbs)	230kg(507lbs)
Lift Extension Capacity	115kg(254lbs)	120kg(265lbs)
Drive Speed-Stowed	4km/h(2.5mph)	4km/h(2.5mph)
Drive Speed-Raised	0.8km/h(0.5mph)	0.8km/h(0.5mph)
Lift Time(Unloaded)	20s~23s	26s
Descent Time(Unloaded)	25s~27s	24s
Gradeability	25%	25%
Turning Radius(Inside/Outside)	0.3m/1.35m(1'/4'5")	0.45m/1.6m(1'6"/5'3")
Tilt Rating(Front to Back/Side to Side)	3°/1.5°	3°/1.5°
Tyre Size/Type	255x76mm (10x3")/solid	255x76mm (10x3.2")/solid
Power		
Batteries	2x12 V,115 Ah	2x12 V,115 Ah
Power Source	24V DC	24V DC
Drive Mode	Motor, Front wheel	Motor, Front wheel
Charger Input	100~240V AC	100~240V AC
Charger Output	15A	15A
Hydraulic Tank Capacity	4L(0.9 gal (UK)/1.05 gal(US))	4 L (0.9 gal(UK)/1.05 gal(US))
Weight		
Weight	880kg(1,941lbs)	1,210kg(2,668lbs)
Standards	ISO/CE/EAC	

